

KAPACITIVNI SENZORI BALLUFF- SIE SENSORIK

Veliki asortiman senzora

- detekcija predmeta sa dometima do 25 mm sensorima u PVC ili metalnom kucistu SK1
- kontrola nivoa tecnosti za standardne aplikacije na atmosferskom pritisku i za povisene pritiske do 10 bari i povisene temperature do 125 C SK1
- kontrola nivoa tecnosti za specijalne aplikacije sa autokalibracijom za pritiske do 10 bari SK1-FSA
- senzori za povisene temperature do 180C i do 255C bez pojacavaca SK1-HT
- NAMUR mini senzori bez pojacavaca za snizene napone (4...8)V SK
- pojacavaci za SK1-HT i SK senzore
- analogni senzor za merenje rastojanja do 8 mm

Zajednički podaci

Radni napon 10...30 VDC Max. pad napona:2V, ponovljivost <2%, stepen mehaničke zaštite: IP65 do IP 68 , zaštita od kratkog spoja i suprotnog polariteta- da

izgled	domet (mm) i način ugradnje	materijal kucista	dimenzije (mm)	izlaz	izlazna struja mA	Frekvencija Hz	radna temperatura	priključak	tip	
DETEKCIJA PREDMETA										
CILINDRICNI OBLIK M8... fi 50mm										
	0,1..1,50	O metal	fi 6,5 x 42	PNP, NO	50	100	-10+70	Kabl 2m	SK1-1.5-6.5-PBS-VA/PTFE	
	0,1..1,50	O metal	fi 6,5 x 42	PNP, NC	50	100	-10+70	Kabl 2m	SK1-1.5-6.5-PBO -VA/PTFE	
	0,1..1,50	O metal	fi 6,5 x 42	NPN, NO	50	100	-10+70	Kabl 2m	SK1-1.5-6.5-NBS-VA/PTFE	
	0,1..1,50	O metal	fi 6,5 x 42	NPN, NC	50	100	-10+70	Kabl 2m	SK1-1.5-6.5-NBO-VA/PTFE	
	0,1..1,5 O	metal	fi 6,5 x 54	PNP, NO	50	100	-10+70	Konektor M8	SK1-1.5-6.5-PBS-VA/PTFE-Y1	
	0,1..1,5 O	metal	fi 6,5 x 54	PNP, NC	50	100	-10+70	Konektor M8	SK1-1.5-6.5-PBO-VA/PTFE-Y1	
	0,1..1,5 O	metal	fi 6,5 x 54	NPN, NO	50	100	-10+70	Konektor M8	SK1-1.5-6.5-NBS-VA/PTFE-Y1	
	0,1..1,5 O	metal	fi 6,5 x 54	NPN, NC	50	100	-10+70	Konektor M8	SK1-1.5-6.5-NBO-VA/PTFE-Y1	
	0,1..3 NO	metal	fi 6,5 x 42	PNP, NO	50	100	-10+70	Kabl 2m	SK1-3-6.5-PNBS-VA/PTFE	
	0,1..3 NO	metal	fi 6,5 x 42	PNP, NC	50	100	-10+70	Kabl 2m	SK1-3-6.5-PNBO-VA/PTFE	
	0,1..3 NO	metal	fi 6,5 x 42	NPN, NO	50	100	-10+70	Kabl 2m	SK1-3-6.5-NNBS-VA/PTFE	
	0,1..3 NO	metal	fi 6,5 x 42	NPN, NC	50	100	-10+70	Kabl 2m	SK1-3-6.5-NNBO-VA/PTFE	
	0,1..3 NO	metal	fi 6,5 x 54	PNP, NO	50	100	-10+70	Konektor M8	SK1-3-6.5- PNBS-VA/PTFE-Y1	
	0,1..3 NO	metal	fi 6,5 x 54	PNP, NC	50	100	-10+70	Konektor M8	SK1-3-6.5- PNBO-VA/PTFE-Y1	
	0,1..3 NO	metal	fi 6,5 x 54	NPN, NO	50	100	-10+70	Konektor M8	SK1-3-6.5- NNBS-VA/PTFE-Y1	
	0,1..3 NO	metal	fi 6,5 x 54	NPN, NC	50	100	-10+70	Konektor M8	SK1-3-6.5- NNBO-VA/PTFE-Y1	
	0,1..1,5 O	metal	M8 x 36/42	PNP, NO	50	100	-10+70	Kabl 2m	SK1-1.5-M8-PBS-VA/PTFE	
	0,1..1,5 O	metal	M8 x 36/42	PNP, NC	50	100	-10+70	Kabl 2m	SK1-1.5-M8-PBO-VA/PTFE	
	0,1..1,5 O	metal	M8 x 36/42	NPN, NO	50	100	-10+70	Kabl 2m	SK1-1.5-M8-NBS-VA/PTFE	
	0,1..1,5 O	metal	M8 x 36/42	NPN, NC	50	100	-10+70	Kabl 2m	SK1-1.5-M8-NBO-VA/PTFE	
	0,1..1,5 O	metal	M8 x 42/54	PNP, NO	50	100	-10+70	Konektor M8	SK1-1.5-M8-PBS-VA/PTFE-Y1	
	0,1..1,5 O	metal	M8 x 42/54	PNP, NC	50	100	-10+70	Konektor M8	SK1-1.5-M8-PBO-VA/PTFE-Y1	
	0,1..1,5 O	metal	M8 x 42/54	NPN, NO	50	100	-10+70	Konektor M8	SK1-1.5-M8-NBS-VA/PTFE-Y1	
	0,1..1,5 O	metal	M8 x 42/54	NPN, NC	50	100	-10+70	Konektor M8	SK1-1.5-M8-NBO-VA/PTFE-Y1	
	0,1..3NO	metal	M8 x 36/42	PNP, NO	50	100	-10+70	Kabl 2m	SK1-3-M8-PNBS-VA/PTFE	
	0,1..3NO	metal	M8 x 36/42	PNP, NC	50	100	-10+70	Kabl 2m	SK1-3-M8-PNBO-VA/PTFE	

	0,1..3NO	metal	M8 x 36/42	NPN, NO	50	100	-10+70	Kabl 2m	SK1-3-M8-NNBS-VA/PTFE	
	0,1..3NO	metal	M8 x 36/42	NPN, NC	50	100	-10+70	Kabl 2m	SK1-3-M8-NNBO-VA/PTFE	
	0,1..3NO	metal	M8 x 42/54	PNP, NO	50	100	-10+70	Konektor M8	SK1-3-M8-PNBS-VA/PTFE-Y1	
	0,1..3NO	metal	M8 x 42/54	PNP, NC	50	100	-10+70	Konektor M8	SK1-3-M8-PNBO-VA/PTFE-Y1	
	0,1..3NO	metal	M8 x 42/54	NPN, NO	50	100	-10+70	Konektor M8	SK1-3-M8-NNBS-VA/PTFE-Y1	
	0,1..3NO	metal	M8 x 42/54	NPN, NC	50	100	-10+70	Konektor M8	SK1-3-M8-NNBO-VA/PTFE-Y1	
	1..4 O	metal	fi 10 x 50	PNP, NO	200	100	-30+70	Kabl 2m	SK1-4-10-PBS-VA/PTFE	
	1..4 O	metal	fi 10 x 50	PNP, NC	200	100	-30+70	Kabl 2m	SK1-4-10-PBO-VA/PTFE	
	1..4 O	metal	fi 10 x 50	NPN, NO	200	100	-30+70	Kabl 2m	SK1-4-10-NBS-VA/PTFE	
	1..4 O	metal	fi 10 x 50	NPN, NC	200	100	-30+70	Kabl 2m	SK1-4-10-NBO-VA/PTFE	
	1..4 O	pvc	M12 x40/ 50	PNP, NO	200	100	-30+60	Kabl 2m	SK1-4-M12-PBS-PVC	
	1..4 O	pvc	M12 x40/ 50	PNP, NC	200	100	-30+60	Kabl 2m	SK1-4-M12-PBO-PVC	
	1..4 O	pvc	M12 x40/ 50	NPN, NO	200	100	-30+60	Kabl 2m	SK1-4-M12-NBS-PVC	
	1..4 O	pvc	M12 x40/ 50	NPN, NC	200	100	-30+60	Kabl 2m	SK1-4-M12-NBO-PVC	
	1..4 O	pvc	M12 x43/ 60	PNP, NO	200	100	-30+60	Konektor M12	SK1-4-M12-PBS- PVC-Y2	
	1..4 O	pvc	M12 x43/ 60	PNP, NC	200	100	-30+60	Konektor M12	SK1-4-M12-PBO- PVC-Y2	
	1..4 O	pvc	M12 x43/ 60	NPN, NO	200	100	-30+60	Konektor M12	SK1-4-M12-NBS- PVC-Y2	
	1..4 O	pvc	M12 x43/ 60	NPN, NC	200	100	-30+60	Konektor M12	SK1-4-M12-NBO- PVC-Y2	
	1..4 O	metal	M12 x40/ 50	PNP, NO	200	100	-30+70	Kabl 2m	SK1-4-M12-PBS-VA/PTFE	
	1..4 O	metal	M12 x40/ 50	PNP, NC	200	100	-30+70	Kabl 2m	SK1-4-M12-PBO-VA/PTFE	
	1..4 O	metal	M12 x40/ 50	NPN, NO	200	100	-30+70	Kabl 2m	SK1-4-M12-NBS-VA/PTFE	
	1..4 O	metal	M12 x40/ 50	NPN, NC	200	100	-30+70	Kabl 2m	SK1-4-M12-NBO-VA/PTFE	
	2..8 O	pvc	M18 x55/ 65	PNP, NO	300	100	-30+60	Kabl 2m	SK1-8-M18-PBS- PVC	
	2..8 O	pvc	M18 x55/ 65	PNP, NC	300	100	-30+60	Kabl 2m	SK1-8-M18-PBO- PVC	
	2..8 O	pvc	M18 x55/ 65	NPN, NO	300	100	-30+60	Kabl 2m	SK1-8-M18-NBS- PVC	
	2..8 O	pvc	M18 x55/ 65	NPN, NC	300	100	-30+60	Kabl 2m	SK1-8-M18-NBO- PVC	
	2..8 O	pvc	M18 x55/ 75	PNP, NO	300	100	-30+60	Konektor M12	SK1-8-M18-PBS- PVC- Y2	
	2..8 O	pvc	M18 x55/ 75	PNP, NC	300	100	-30+60	Konektor M12	SK1-8-M18-PBO- PVC- Y2	
	2..8 O	pvc	M18 x55/ 75	NPN, NO	300	100	-30+60	Konektor M12	SK1-8-M18-NBS- PVC- Y2	
	2..8 O	pvc	M18 x55/ 75	NPN, NC	300	100	-30+60	Konektor M12	SK1-8-M18-NBO- PVC- Y2	
	2..8 O	metal	M18 x55/ 65	PNP, NO	300	100	-30+70	Kabl 2m	SK1-8-M18-PBS- VA/PBT	
	2..8 O	metal	M18 x55/ 65	PNP, NC	300	100	-30+70	Kabl 2m	SK1-8-M18-PBO- VA/PBT	
	2..8 O	metal	M18 x55/ 65	NPN, NO	300	100	-30+70	Kabl 2m	SK1-8-M18-NBS- VA/PBT	
	2..8 O	metal	M18 x55/ 65	NPN, NC	300	100	-30+70	Kabl 2m	SK1-8-M18-NBO- VA/PBT	
	2..8 O	metal	M18 x54/ 75	PNP, NO	300	100	-30+70	Konektor M12	SK1-8-M18-PBS- VA/PBT-Y2	
	2..8 O	metal	M18 x54/ 75	PNP, NC	300	100	-30+70	Konektor M12	SK1-8-M18-PBO- VA/PBT-Y2	
	2..8 O	metal	M18 x54/ 75	NPN, NO	300	100	-30+70	Konektor M12	SK1-8-M18-NBS- VA/PBT-Y2	
	2..8 O	metal	M18 x54/ 75	NPN, NC	300	100	-30+70	Konektor M12	SK1-8-M18-NBO- VA/PBT-Y2	
	2..10 O	metal	f22 x 65	PNP, NO	300	100	-30+60	Kabl 2m	SK1-10-22-PBS- VA/PVC	
	2..10 O	metal	f22 x 65	PNP, NC	300	100	-30+60	Kabl 2m	SK1-10-22-PBO- VA/PVC	
	2..10 O	metal	f22 x 65	NPN, NO	300	100	-30+60	Kabl 2m	SK1-10-22-NBS- VA/PVC	
	2..10 O	metal	f22 x 65	NPN, NC	300	100	-30+60	Kabl 2m	SK1-10-22-NBO- VA/PVC	
	2..20 O	metal	f30 x 66	PNP, NO/NC	300	100	-30+70	Kabl 2m	SK1-20-30-PBX- VA/PBT	
	2..20 O	metal	f30 x 66	NPN, NO/NC	300	100	-30+70	Kabl 2m	SK1-20-30-NBX- VA/PBT	
	1..20 O	pvc	M30 x 66	PNP, NO/NC	300	100	-30+70	Kabl 2m	SK1-20-M30-PBX- PBT	
	1..20 O	pvc	M30 x 66	NPN, NO/NC	300	100	-30+70	Kabl 2m	SK1-20-M30-NBX- PBT	
	1..20 O	pvc	M30 x 66	PNP, NO/NC	300	100	-30+70	Konektor M12	SK1-20-M30-PBX- PBT-Y2	
	1..20 O	pvc	M30 x 66	NPN, NO/NC	300	100	-30+70	Konektor M12	SK1-20-M30-NBX- PBT-Y2	
	1..20 O	metal	M30 x 66	PNP, NO/NC	300	100	-30+70	Kabl 2m	SK1-20-M30-PBX- VA/PBT	
	1..20 O	metal	M30 x 66	NPN, NO/NC	300	100	-30+70	Kabl 2m	SK1-20-M30-NBX- VA/PBT	
	1..20 O	metal	M30 x 66	PNP, NO/NC	300	100	-30+70	Konektor M12	SK1-20-M30-PBX- VA/PBT-Y2	

	1..20 O	metal	M30 x 66	NPN, NO/NC	300	100	-30+70	Konektor M12	SK1-20-M30-NBX- VA/PBT-Y2	
	1..25 O	pvc	f34 x 66	PNP, NO/NC	300	100	-30+60	Kabl 2m	SK1-25-34-PBX- PVC	
	1..25 O	pvc	f34 x 66	NPN, NO/NC	300	100	-30+60	Kabl 2m	SK1-25-34-NBX- PVC	
	1..25 O	pvc	f34 x 66	PNP, NO/NC	300	100	-30+60	Konektor M12	SK1-25-34-PBX- PVC-Y2	
	1..25 O	pvc	f34 x 66	NPN, NO/NC	300	100	-30+60	Konektor M12	SK1-25-34-NBX- PVC-Y2	

OBLIK DISKA fi 22 do fi 50 mm

	6+- 10%	metal	fi 22 x 4	PNP, NO	300	100	-30+70	Kabl 2m	SK1-6F-22/4-PBS-VA/PTFE	
	6+- 10%	metal	fi 22 x 4	NPN, NO	300	100	-30+70	Kabl 2m	SK1-6F-22/4-NBS-VA/PTFE	
	2...15	metal	fi 30 x 4	PNP, NO	300	100	-30+70	Kabl 2m	SK1-15-30/4-PBS-VA/PTFE	
	2...15	metal	fi 30 x 4	PNP, NC	300	100	-30+70	Kabl 2m	SK1-15-30/4-PBO-VA/PTFE	
	2...15	metal	fi 30 x 4	NPN, NO	300	100	-30+70	Kabl 2m	SK1-15-30/4-NBS-VA/PTFE	
	2...15	metal	fi 30 x 4	NPN, NC	300	100	-30+70	Kabl 2m	SK1-15-30/4-NBO-VA/PTFE	
	2...25	pvc	fi 50 x 10	PNP + NPN, NO+ NZ	150	100	-30+60	Kabl 2m	SK1-25-50/10-XXB-POM	
	2...25	pvc	fi 50 x 10	PNP + NPN, NO+ NZ	150	100	-30+60	Konektor M8	SK1-25-50/10-XXB-POM-Y1	

PRAVOUGAONI OBLIK 34 x 16 x 8 mm

	1.8 O	PVC	34 X 16 X 8	PNP, NO	50	100	-30+70	Konektor M8	SK1-8-34/16/8-PBS- PP	
	1.8 O	PVC	34 X 16 X 8	PNP, NC	50	100	-30+70	Konektor M8	SK1-8-34/16/8-PBO- PP	
	1.8 O	PVC	34 X 16 X 8	NPN, NO	50	100	-30+70	Konektor M8	SK1-8-34/16/8-NBS- PP	
	1.8 O	PVC	34 X 16 X 8	NPN, NC	50	100	-30+70	Konektor M8	SK1-8-34/16/8-NBO- PP	
	1.8 O	PVC	34 X 16 X 8	PNP, NO	50	100	-30+70	Konektor M8	SK1-8-34/16/8-PBS- PP/Y1	
	1.8 O	PVC	34 X 16 X 8	PNP, NC	50	100	-30+70	Konektor M8	SK1-8-34/16/8-PBO- PP/Y1	
	1.8 O	PVC	34 X 16 X 8	NPN, NO	50	100	-30+70	Konektor M8	SK1-8-34/16/8-NBS- PP/Y1	
	1.8 O	PVC	34 X 16 X 8	NPN, NC	50	100	-30+70	Konektor M8	SK1-8-34/16/8-NBO- PP/Y1	

DETEKCIJA NIVOA

cilindricni- za povisene pritiske 10 bari IP 68

	FS/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	Kabl 2m	SK1-FS-MLM12-XDC-PSU	
	FS/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	Kabl 2m	SK1-FS-MLG1/4-XDC-PSU	
	FS/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	Kabl 2m	SK1-FS-MLNPT1/4-XDC-PSU	
	FS/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	konektor M8	SK1-FS-MLM12-XDC-PSU-Y1	
	FS/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	konektor M8	SK1-FS-MLG1/4-XDC-PSU-Y1	
	FS/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	konektor M8	SK1-FS-MLNPT1/4-XDC-PSU-Y1	
	FS/NO	pvc	fi 7 x 12+ SW14x15 +M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	konektor M8	SK1-FS-MLRM12-XDC-PSU-Y1	
	FS/NO	pvc	fi 7 x 12+ SW14x15 +M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	konektor M8	SK1-FS-MLRM12-XDC-PSU-Y1	
	FS/NO	pvc	fi 7 x 12+ SW14x15 +M12x15	PNP + NPN, NO+ NZ	50	5	-10+70	konektor M8	SK1-FS-MLRM12-XDC-PSU-Y1	

Opcije- navoj za montazu senzora : M12 ili G1 1/4" ili NPT 1/4", domet- FS (detektor napunjenosti)

cilindricni- za atmosferski pritisak IP 65

	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	kabl 2m	SK1-8-M12-PNBS- PVC	
	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	kabl 2m	SK1-8-M12-PNBO- PVC	
	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	kabl 2m	SK1-8-M12-NNBS- PVC	
	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	kabl 2m	SK1-8-M12-NNBO- PVC	
	1..6 NO	PVC	M12x50/60	PNP ili NPN, NOili NZ	200	25	-30+60	kabl 2m	SK1-TM-6-M12/60-PNBS- PVC	
	1..6 NO	PVC	M12x50/60	PNP ili NPN, NOili NZ	200	25	-30+60	kabl 2m	SK1-TM-6-M12/60-PNBO- PVC	
	1..6 NO	PVC	M12x50/60	PNP ili NPN, NOili NZ	200	25	-30+60	kabl 2m	SK1-TM-6-M12/60-NNBS- PVC	
	1..6 NO	PVC	M12x50/60	PNP ili NPN, NOili NZ	200	25	-30+60	kabl 2m	SK1-TM-6-M12/60-NNBO- PVC	
	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	konektor M12	SK1-8-M12-PNBS- PVC-Y2	
	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	konektor M12	SK1-8-M12-PNBO- PVC-Y2	

	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	konektor M12	SK1-8-M12-NNBS- PVC-Y2	
	1..8 NO	PVC	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+60	konektor M12	SK1-8-M12-NNBO- PVC-Y2	
	1..8 NO	metal	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-PNBS- VA/PTFE	
	1..8 NO	metal	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-PNBO- VA/PTFE	
	1..8 NO	metal	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-NNBS- VA/PTFE	
	1..8 NO	metal	M12x40/50	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-NNBO- VA/PTFE	
	1..8 NO	metal	M12x50/60	PNP ili NPN, NOili NZ	200	100	-30+70	konektor M12	SK1-8-M12-PNBS- VA/PTFE-Y2	
	1..8 NO	metal	M12x50/60	PNP ili NPN, NOili NZ	200	100	-30+70	konektor M12	SK1-8-M12-PNBO- VA/PTFE-Y2	
	1..8 NO	metal	M12x50/60	PNP ili NPN, NOili NZ	200	100	-30+70	konektor M12	SK1-8-M12-NNBS- VA/PTFE-Y2	
	1..8 NO	metal	M12x50/60	PNP ili NPN, NOili NZ	200	100	-30+70	konektor M12	SK1-8-M12-NNBO- VA/PTFE-Y2	
	1..6 NO	PVC	M12x43/53	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-PNBS- CPTFE	
	1..6 NO	PVC	M12x43/53	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-PNBO- CPTFE	
	1..6 NO	PVC	M12x43/53	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-NNBS- CPTFE	
	1..6 NO	PVC	M12x43/53	PNP ili NPN, NOili NZ	200	100	-30+70	kabl 2m	SK1-8-M12-NNBO- CPTFE	
	2..15 NO	PVC	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+60	kabl 2m	SK1-15-M18-PNBS- PVC	
	2..15 NO	PVC	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+60	kabl 2m	SK1-15-M18-PNBO- PVC	
	2..15 NO	PVC	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+60	kabl 2m	SK1-15-M18-NNBS- PVC	
	2..15 NO	PVC	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+60	kabl 2m	SK1-15-M18-NNBO- PVC	
	2..15 NO	PVC	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+60	konektor M12	SK1-15-M18-PNBS- PVC-Y2	
	2..15 NO	PVC	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+60	konektor M12	SK1-15-M18-PNBO- PVC-Y2	
	2..15 NO	PVC	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+60	konektor M12	SK1-15-M18-NNBS- PVC-Y2	
	2..15 NO	PVC	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+60	konektor M12	SK1-15-M18-NNBO- PVC-Y2	
	2..15 NO	metal	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-PNBS- VA/PTFE	
	2..15 NO	metal	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-PNBO- VA/PTFE	
	2..15 NO	metal	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-NNBS- VA/PTFE	
	2..15 NO	metal	M18x50/65	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-NNBO- VA/PTFE	
	2..15 NO	metal	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+70	konektor M12	SK1-15-M18-PNBS-VA/PTFE-Y2	
	2..15 NO	metal	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+70	konektor M12	SK1-15-M18-PNBO-VA/PTFE-Y2	
	2..15 NO	metal	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+70	konektor M12	SK1-15-M18-NNBS-VA/PTFE-Y2	
	2..15 NO	metal	M18x60/75	PNP ili NPN, NOili NZ	300	100	-30+70	konektor M12	SK1-15-M18-NNBO-VA/PTFE-Y2	
	2..15 NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-PNBS- CPTFE	
	2..15 NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-PNBO- CPTFE	
	2..15 NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-NNBS- CPTFE	
	2..15 NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-15-M18-NNBO- CPTFE	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	kabl 2m	SK1-30-M30-PNBX- PBT	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	kabl 2m	SK1-30-M30-NNBX- PBT	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	konektor M12	SK1-30-M30-PNBX- PBT-Y2	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	konektor M12	SK1-30-M30-NNBX- PBT-Y2	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	kabl 2m	SK1-30-M30-PNBX-VA/ PTFE	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	kabl 2m	SK1-30-M30-NNBX-VA/ PTFE	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	konektor M12	SK1-30-M30-PNBX-VA/ PTFE-Y2	
	1..30 NO	PVC	M30x38/66	PNP ili NPN, NO+ NZ	300	100	-30+70	konektor M12	SK1-30-M30-NNBX-VA/ PTFE-Y2	
	2..30 NO	PVC	M30x52/72	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-30-M30-PNBS- CPTFE	
	2..30 NO	PVC	M30x52/72	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-30-M30-PNBO- CPTFE	
	2..30 NO	PVC	M30x52/72	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-30-M30-NNBS- CPTFE	
	2..30 NO	PVC	M30x52/72	PNP ili NPN, NOili NZ	300	100	-30+70	kabl 2m	SK1-30-M30-NNBO- CPTFE	
cilindricni sa glavom- za povisene temperature i pritiske, -30 do 125 C 10 bari IP67/ IP 68										
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JM18-PS-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JM18-PO-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JM18-NS-VA/ PTFE	

		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JM18-NO-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JR3/8-PS-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JR3/8-PO-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JR3/8-NS-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-JR3/8-NO-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-J3/8NPTF-PS-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-J3/8NPTF-PO-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-J3/8NPTF-NS-VA/ PTFE	
		PVC	fi 12 x35+fi 44 x60	PNP ili NPN, NOili NZ	100	5	-30+125	uvodnica m16	SK1-HT125-FS-J3/8NPTF-NO-VA/ PTFE	

DETEKCIJA NIVOVA - sa autokalibracijom za penu i isparenja

	NO	pvc	fi 7 x 52	PNP ili NPN, NOili NZ	50	10	+5..+100	Kabl 2m	SK1-FSA-D7B9/52-PNBS-CPTFE	
	NO	pvc	fi 7 x 52	PNP ili NPN, NOili NZ	50	10	+5..+100	Kabl 2m	SK1-FSA-D7B9/52-PNBO-CPTFE	
	NO	pvc	fi 7 x 52	PNP ili NPN, NOili NZ	50	10	+5..+100	Kabl 2m	SK1-FSA-D7B9/52-NNBS-CPTFE	
	NO	pvc	fi 7 x 52	PNP ili NPN, NOili NZ	50	10	+5..+100	Kabl 2m	SK1-FSA-D7B9/52-NNBO-CPTFE	

cilindricni- za povisene pritiske 10 bari IP 68


	FSA/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	Kabl 2m	SK1-FSA-MLM12-XDC-PSU	
	FSA/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	Kabl 2m	SK1-FSA-MLG1/4-XDC-PSU	
	FSA/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	Kabl 2m	SK1-FSA-MLNPT1/4-XDC-PSU	
	FSA/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	100	-10+105	Kabl 2m	SK1-FSA- MLM12-XDCS-PSU	
	FSA/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	100	-10+105	Kabl 2m	SK1-FSA- MLG1/4-XDCS-PSU	
	FSA/NO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	100	-10+105	Kabl 2m	SK1-FSA- MLNPT1/4-XDCS-PSU	
	FSANO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	konektor M8	SK1-FSA- MLM12-XDCS-PSU-Y1	
	FSANO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	konektor M8	SK1-FSA- MLG1/4-XDCS-PSU- Y1	
	FSANO	pvc	fi 7 x 12+M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	konektor M8	SK1-FSA- MLNPT1/4-XDCS- PSU-Y1	
	FSANO	pvc	fi 7 x 12+ SW14x15 +M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	konektor M8	SK1-FSA- MLRM12-XDC-PSU-Y1	
	FSANO	pvc	fi 7 x 12+ SW14x15 +M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	konektor M8	SK1-FSA- MLRG1/4-XDC-PSU- Y1	
	FSANO	pvc	fi 7 x 12+ SW14x15 +M12x15	PNP + NPN, NO+ NZ	50	5	-10+105	konektor M8	SK1-FSA- MLRNPT1/4-XDC- PSU-Y1	

cilindricni- za atmosferski pritisak IP 65

	FSA/NO	pvc	M18x48/65	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-PNBS- PVC	
	FSA/NO	pvc	M18x48/65	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-PNBO- PVC	
	FSA/NO	pvc	M18x48/65	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-NNBS- PVC	
	FSA/NO	pvc	M18x48/65	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-NNBO- PVC	
	FSA/NO	pvc	M18x55/70	PNP ili NPN, NOili NZ	300	2	-10+60	konektor M8	SK1-FSA-M18-PNBS- PVC-Y1	
	FSA/NO	pvc	M18x55/70	PNP ili NPN, NOili NZ	300	2	-10+60	konektor M8	SK1-FSA-M18-PNBO- PVC-Y1	
	FSA/NO	pvc	M18x55/70	PNP ili NPN, NOili NZ	300	2	-10+60	konektor M8	SK1-FSA-M18-NNBS- PVC-Y1	
	FSA/NO	pvc	M18x55/70	PNP ili NPN, NOili NZ	300	2	-10+60	konektor M8	SK1-FSA-M18-NNBO- PVC-Y1	
	FSA/NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-PNBS- CPTFE	
	FSA/NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-PNBO- CPTFE	
	FSA/NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-NNBS- CPTFE	
	FSA/NO	pvc	M18x58/73	PNP ili NPN, NOili NZ	300	2	-10+60	kabl 2m	SK1-FSA-M18-NNBO- CPTFE	
	FSA/NO	pvc	M30x45/65	PNP ili NPN, NO+NZ	300	2	-10+60	konektor M12	SK1-FSA-M30-PNBX- PBT-Y2	
	FSA/NO	pvc	M30x45/65	PNP ili NPN, NO+NZ	300	2	-10+60	konektor M12	SK1-FSA-M30-NNBX- PBT-Y2	
	FSA/NO	pvc	M30x52/72	PNP ili NPN, NO+NZ	300	2	-10+60	kabl 2m	SK1-FSA-M30-PNBS- CPTFE	

	FSA/NO	pvc	M30x52/72	PNP ili NPN, NO+NZ	300	2	-10+60	kabl 2m	SK1-FSA-M30-PNBO- CPTFE	
	FSA/NO	pvc	M30x52/72	PNP ili NPN, NO+NZ	300	2	-10+60	kabl 2m	SK1-FSA-M30-NNBS- CPTFE	
	FSA/NO	pvc	M30x52/72	PNP ili NPN, NO+NZ	300	2	-10+60	kabl 2m	SK1-FSA-M30-NNBO- CPTFE	
OBLIK DISKA										
	FSA/O	pvc	fi 50 x 10	PNP ili NPN, NO+ NZ	300	2	-10+60	Kabl 2m	SK1-FSA-50/10-PBX-POM	
	FSA/O	pvc	fi 50 x 10	PNP ili NPN, NO+ NZ	300	2	-10+60	Kabl 2m	SK1-FSA-50/10-NBX-POM	
	FSA/O	PTFE	fi 50 x 10	PNP ili NPN, NOili NZ	300	2	-10+60	Kabl 2m	SK1-FSA-50/10-PBS-CPTFE	
	FSA/O	PTFE	fi 50 x 10	PNP ili NPN, NOili NZ	300	2	-10+60	Kabl 2m	SK1-FSA-50/10-PBO-CPTFE	
	FSA/O	PTFE	fi 50 x 10	PNP ili NPN, NOili NZ	300	2	-10+60	Kabl 2m	SK1-FSA-50/10-NBS-CPTFE	
	FSA/O	PTFE	fi 50 x 10	PNP ili NPN, NOili NZ	300	2	-10+60	Kabl 2m	SK1-FSA-50/10-NBO-CPTFE	
PRAVOUGAONI OBLIK										
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 2m	SK1-FSA-34/16/8-PBS- PP	
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 2m	SK1-FSA-34/16/8-PBO- PP	
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 2m	SK1-FSA-34/16/8-NBS- PP	
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 2m	SK1-FSA-34/16/8-NBO- PP	
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 0.2m+ konektor M8	SK1-FSA-34/16/8-PBS- PP-M2/Y1	
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 0.2m+ konektor M8	SK1-FSA-34/16/8-PBO- PP-M2/Y1	
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 0.2m+ konektor M8	SK1-FSA-34/16/8-NBS- PP-M2/Y1	
	FSA/O	PVC	34 X 16 X 8	PNP ili NPN, NOili NZ	50	2	-30+70	Kabl 0.2m+ konektor M8	SK1-FSA-34/16/8-NBO- PP-M2/Y1	
Opcije- navoj za montazu senzora : M12 ili G1 /4" ili NPT 1/4", domet- FSA (detektor napunjenosti),CST- sa test signalom										
ANALOGNI SENZOR korekcionni faktori- celik, voda, mesing-1, papir-0,7, pvc- 0,4										
	0.8 O	metal	M18x65	4...20mA	4..20	100	+10+55	Kabl 2m	SK1-A-8-M18-4I20-B-VA/PBT	
SENZORI ZA POVISENE TEMPERATURE do 180C i do 250C bez pojacavaca										
	1..10 NO	metal	M18x45/65			2	-180+250		SK-HT250-10-M18-NB-VA/PTFE	
	1..20 NO	metal	M30x37/65			2	-180+250		SK-HT250-20-M30-NB-VA/PTFE	
	NO	metal	M18x12/57				-10+180		SK-HT180-FS-M18- VA/PTFE	
	NO	metal	M18x12/57				-10+180		SK-HT180- FS- B ₂ /s-VA/PTFE	
	NO	metal	M18x12/57				-10+180		SK-HT180- FS- I ₂ /s-NPT-VA/PTFE	
			fi 9x35				-10+70		SLK-HT	
POJACAVACI ZA SENZORE										
	kontrola u 1 tacki		99x 75 x 22	rele 8A		10	-30+70	230(110)VAC	SNG-230AC/24DC-T	
	kontrola u 2 tacke		99x 75 x 22	rele 8A		5	-30+70	230(110)VAC	SNG-230AC/MINMAX	
NAMUR SENZORI bez pojacavaca 4...8 V										
PRIBOR ZA SENZORE										
	DRZAC SENZORA		F118/fi22/fi30/fi34						MB-18/22/30/34	
	konektor M8 ravan		fi 8,5 x 30					kabl 2m	Z 10	
	konektor M8 ugaoni		fi 8,5 x14x20					kabl 2m	Z 11	
	konektor M12 ravan		fi 14,5 x 42					kabl 2m	Z 20	
	konektor M12 ugaoni		fi 14,5 x26x39					kabl 2m	Z21	
	konektor za SLK-HT		fi 8 x 19					kabl 2m	SL-YA-M20	

Korektivni faktori za domet na razlicite materijale: metal, voda- 1,PVC- 0,6, drvo 0,2...0,7, staklo- 0,5, ulje – 0,1
 Podebljana i podvucena slova u tipskoj oznaci imaju sledece znacenje za izlaznu funkciju senzora:
 Prvo slovo (PNP ili NPN) - **P** - PNP izlaz, **N** - NPN izlaz,
 drugo slovo (NO ili NZ): NO –normalno otvoren kontakt, NZ- normalno zatvoren kontakt
 Simboli u tabeli
 kolona **domet**: o - oklopljen, n- neoklopljen;
 kolona **materijal** : p- prohrom, m- mesing niklovan



ENEL d.o.o.
INDUSTRIJSKA AUTOMATIKA

14000 VALJEVO

Vasilja Pavlovića 10

Fax:014 244-641 Tel:291-1610, 291-161

e-mail:enelva@ptt.yu; www.enelva.co.yu

PIB:100071471 T.R. 170-425-97