



Capacitive Mini-sensors, SK

- Housings in V2A/PTFE from Ø 4 mm
- Flat disk form from Ø 18 mm by only 2.5 mm high
- Sensing distance adjustable on the amplifier
- Variety of processing electronics available




Capacitive sensors for object detection, SK1-B

- Housings made of metal or plastic
- Compact sizes with potentiometer starting at Ø 6.5 mm
- Disc sizes up to Ø 50 mm
- Sensing distance up to 25 mm
- Flush mounting
- Connecting lead or plug connector



Capacitive sensors for level sensing, SK1-NB

- Housings M12 and larger in metal, plastic and PTFE
- Cable, connector and terminal versions available
- Operating temperature up to 125 °C at 10 bar pressure rating
- Dependable switching for granules, powders and liquids



Sensors for level sensing

Capacitive smartLEVEL sensors, FSA

- For aqueous media
- No adjustment in standard application
- Self-compensating
- Through glass or plastic
- Flush and non-flush versions



Sensors for level sensing

Capacitive microBOX sensors

- As sensors for object detection of in smartLEVEL technology
- Compact housing design
- Variety of mounting options
- Mounting bracket included
- Polypropylene housing
- 3-D cable exit

Table of Contents

Page

Capacitive sensors –
general description

**1.02 –
1.10**

Mini-sensors

**3.01 –
3.09**

Sensor amplifiers

**4.01 –
4.05**

Sensors for
object detection

**6.01 –
6.15**

Sensors for
level sensing

**7.01 –
7.12**

Sensors for level sensing,
smartLEVEL-Technology

**7.13 –
7.22**

microLEVEL

**7.15 –
7.17**

microBOX

7.21

Analog sensor

**8.01 –
8.04**

Sensors for the high
temperature range

**9.01 –
9.03**

Sensor power packs

**12.01 –
12.03**

Accessories

**13.01 –
13.05**